

L20/480 HINGED HYGIENIC GRP DOORSETS

Dortek F Type Fire Rated Single Action Hinged Door Sets

- Manufacturer : Dortek Limited, St Marks St., Hull HU8 7ED, United Kingdom
Tel: +44 (0) 1482 226 848 Fax + 44 (0) 1482 226 843 email : info@dortek.com
- Door: : The doors shall be of seamless glass fibre reinforced polyester moulded around non-organic hi-density core.
- Reference : Dortek Type F30- or F60- or F120- Single-SA single action
or Pair-SA single action
- Sizes : *See list of manufacturers standard sizes.*
- Core : Vermiculite board, 35mm thick and of 380kg per cubic metre density.
Thermal conductivity 0.05 W/m sq.
- Facing : Seamless hygienic moulded fire retardant polyester 2.5mm thick. Moisture absorption zero.
- Door leaf: 40mm thick.
- Finish : Smooth non-porous fire retardant gel-coat finish with built in colour.
- Colour : Standard Super White 337 *or choice of 20 colours see chart or RAL / BS to order*
- Door frame : Seamless GRP with concealed intumescent strip (patent 334 964) *or* stainless Steel or PPC metal frame to suit wall thickness *specify thickness* with concealed intumescent strip
in door edges. (patent 334 964) *specify with or without smoke seals*
- Fire Rating : As building regulations and fire officer requirement tested to BS 476 part 22
- Ironmongery : Stainless steel lift off hinges, Geze door closers, *specify handles and locks etc*
- Glazing : Triple glazed with laminate safety glass outer panes finished flush with both faces of door, centre pane Georgian wired *or* ceramic glass, (30 & 60 min doors only) *or* Triple glazed with laminate safety glass outer panes finished with 2mm stainless steel frame, centre pane ceramic glass (120 min doors)
Size 200 x 300mm or 200 x 600mm or 300 x 600mm or 400 x 600mm positioned 165mm from leading edge *or other sizes on request*
- Protection : 3mm thick ribbed rubber standard colour grey, *or* 2mm thick smooth finish high impact grey PVC or 0.7mm thick stainless steel, bonded to door leaf
- Fixing : Fix direct to structure with stainless steel screws.